INTELLECTUAL PROPERTY LAW 8110 GATEHOUSE ROAD SHITE 500 EAST FALLS CHURCH, VA 22042-1210

USA

(703) 205-8000

FAX: (703) 205-8050 (703) 698-8590 (G IV)

e-mail: mailroom@bskb.com web: http://www.bskb.com

CALIFORNIA OFFICE 650 TOWN CENTER DRIVE, SUITE 1120 COSTA MESA, CA 92626-7125

GARY D. YACURA
THOMAS S. AUCHTERLONIE
MICHAEL R. CAMMARATA
JAMES T. ELLER, JR.
SCOTT L. LOWE
MARY ANN CAPRIA
MARRY ANN LOPERIA
MARK J. MUELL, PH. D.
DARIN E. BARTHOLOMEW'
PAUL C. LEWIDERSON
W. KARL RENNER
WARK W. MILLSTEAD'
MARK W. MILLSTEAD'
MARK W. MILLSTEAD' MARK W. MILSTEAD* REG. PATENT AGENTS: FREDERICK R. HANDREN ANDREW J. TELESZ, JR. MARYANNE ARMSTRONG, PH.D MARYANNE ARMSTRONG, PH MAKI HATSUMI MIKE S. RYU CRAIG A. McROBBIE GARTH M. DAHLEN, PH.D. LAURA C. LUTZ ROBERT E. GOOZNER, PH.D. HYUNG N SOHN MATTHEW J. LATTIG ALAN PEDERSEN-GII JUSTIN D. KARJALA

Date: January 10, 2000 Docket No.: 0465-0656P-SP

Assistant Commissioner for Patents BOX PATENT APPLICATION

Washington, D.C. 20231

Sir:

40

44

2

C

c

Transmitted herewith for filing is the patent application of

Inventor(s): PARK, Yong C.

For: OPTICAL RECORDING MEDIUM AND MEDIUM FOR FORMATTING

Enclosed are:

X	A	specification	consisting	of	<u>17</u>	pages
---	---	---------------	------------	----	-----------	-------

- 7 sheet(s) of formal drawings
- _X_ An assignment of the invention
- Х Certified copy of Priority Document(s)
- Х Executed Declaration X Original Photocopy
- A verified statement to establish small entity status under 37 CFR 1.9 and 37 CFR 1.27
- Preliminary Amendment
- Information Disclosure Statement, PTO-1449 and reference(s)

___ Other ____

The filing fee has been calculated as shown below:

LARGE ENTITY

SMALL ENTITY

FOR	NO.	FI	LED		NO. EXT	TRA	RAT	E	FEI	G.		F	RATI	3	FEE
BASIC FEE	***	***	***	**		***	,	*	\$690.	.00	or	**	***		\$345.00
TOTAL CLAIMS	9	-	20	=	(0	x18	=\$	0 .	.00	or	x	9	=	\$ 0.00
INDEPENDENT	1	-	3	_		0	x78	=\$	0 .	.00	or	×	39	=	\$ 0.00
MULTIPLE DI CLAIM PRESI			Т	no	<u> </u>		+260) =	\$ 0	.00	or	+3	L30	=	\$ 0.00

TOTAL \$ 690.00

TOTAL \$ 0.00

X A check in the amount of \$ 730.00 to cover the filing fee and recording fee (if applicable) is enclosed.

No fee is enclosed.

If necessary, the Commissioner is hereby authorized in this, concurrent, and future replies, to charge payment or credit any overpayment to Deposit Account No. 02-2448 for any additional fees required under 37 C.F.R. 1.16 or under 37 C.F.R. 1.17; particularly, extension of time fees.

Respectfully submitted,

BIRCH STEWART, KOLASCH & BIRCH, LLP

By Joseph A. Kolasch

Reg. No. 22,463 P. O. Box 747

Falls Church, Virginia 22040-0747

(703) 205-8000 JAK/dll

20

5

OPTICAL RECORDING MEDIUM AND METHOD FOR FORMATTING

BACKGROUND OF THE INVENTION

Field of the Invention

The present invention relates to an optical recording medium and more particularly to a method of formatting a rewritable optical recording medium.

Discussion of Related Art

An optical storage medium is generally divided into a read only memory (ROM), a write once read many (WORM) memory into which data can be written one time, and rewritable memories into which data can be written several times.

Rewritable optical storage mediums, i.e. optical discs, include rewritable compact discs (CD-R) and rewritable digital versatile discs (DVD-R, DVD-RAM, DVD+R).

The operations of writing and playing back data in a rewritable optical disc may be repeated. This repeated process alters the ratio of storage layers for recording data into the optical disc from the initial ratio. Thus, the optical discs lose its characteristics and generate an error during recording/playback. This degradation appears as a defective area at the time of formatting, recording on or playing back

5

from an optical storage medium. Also, defective areas of a rewritable optical disc may be caused by a scratch on its surface, particles of dirt and dust, or errors during manufacture. Therefore, in order to prevent writing into or reading out of the defective area, management of such defective areas is necessary.

FIG. 1 shows a defect management area (DMA) in a lead-in area and a lead-out area of the optical disc to manage a defect area. Particularly, the data area is divided into a plurality of zones for the defect area management, where each zone is further divided into a user area and a spare area. The user area is where data is actually written and the spare area is used when a defect occurs in the user area.

There are four DMAs in one disc, e.g. DVD-RAM, two of which exist in the lead-in area and two exist in the lead-out area. Because managing defective areas is important, the same contents are repeatedly recorded in all four DMAs to protect the data. Each DMA comprises two blocks of 32 sectors, where one block comprises 16 sectors. The first block of the DMA, called a DDS/PDL block, includes a disc definition structure (DDS) and a primary defect list (PDL). The second block of the DMA, called an SDL block, includes a secondary defect list (SDL). The PDL corresponds to a primary defect data storage

5

and the SDL corresponds to a secondary defect data storage.

The PDL generally stores entries of defective sectors caused during the manufacture of the disc or identified when formatting a disc, namely initializing and re-initializing a disc. Each entry is composed of an entry type and a sector number corresponding to a defective sector. The SDL lists defective areas in block units, thereby storing entries of defective blocks occurring after formatting or defective blocks which could not be stored in the PDL during the formatting. Each SDL entry has an area for storing a sector number of the first sector of a block having defective sectors, an area for storing a sector number of the first sector of a block replacing the defective block, and reserved areas. Accordingly, defective areas, i.e. defective sectors or defective blocks, within the data area are replaced with normal or non-defective sectors or blocks by a slipping replacement algorithm and a linear replacement algorithm.

The slipping replacement algorithm is utilized when a defective area is recorded in the PDL. As shown in FIG. 2A, if defective sectors m and n, corresponding to sectors in the user area, are recorded in the PDL, such defective sectors are skipped to the next available sector. By replacing the defective sectors by subsequent sectors, data is written to a

5

normal sector. As a result, the user area into which data is written slips and occupies the spare area in the amount equivalent to the skipped defective sectors. For example, if two defect sectors are registered in the PDL, data would occupy two sectors of the spare area.

The linear replacement algorithm is utilized when a defective block is recorded in the SDL or when a defective block is found during playback. As shown in FIG. 2B, if defective blocks m and n, corresponding to blocks in either the user or spare area, are recorded on the SDL, such defective blocks are replaced by normal blocks in the spare area and the data to be recorded in the defective block are recorded in an assigned spare area.

As defective areas are compensated utilizing the spare area, methods of assigning the spare area plays an important role in the defective area management. Typically, the spare area may be allocated in each zone or group of the data area or may be allocated in a designated portion of the data area. One method is to allocate the spare area at the top of the data area, as shown in FIG. 3. In such case, the spare area is called a Primary Spare Area. Namely, the data area excluding the primary spare area becomes the user area.

The primary spare area, assigned in an initial formatting

2.0

5

process, is assigned when a manufacturer produces the optical disc or when a user initially formats an empty disc. Moreover, when defect sectors are registered in the PDL according to the initial formatting or reformatting of optical disc, data cannot be recorded in those defect sectors, reducing the recording capacity. Therefore, to maintain the initial data recording capacity, a portion of the primary spare area equivalent to the defective sectors registered on the PDL slips into or becomes a part of the user area during formatting. Accordingly, the PSN of the user area to which a value of LSN=0 is assigned varies depending upon the defective sectors registered on the PDL.

If the primary spare area becomes full by slipping or linear replacement, as shown in FIG. 4A, a new spare area may be assigned, for example near the end of the user area. Such additional spare area is called a supplementary spare area (SA-sup). The location information of the supplementary spare area is stored in a specific area such as in the SDL block of the DMA. Particularly, the location information includes the start address (the first sector number) and the end address (the last sector number) of the assigned supplementary spare area. Thus, the size as well as the location of the supplementary spare area can be ascertained from the

5

information.

The assigned supplementary spare area may be enlarged when necessary as shown in FIG. 4B. Also, the location of the extended supplementary spare area is stored in the specific area of the DMA as in the initial assignment of the supplementary spare area. However, since a location information is already stored in the DMA, the start address of the location information is modified. As a result, the location information of the supplementary spare area is modified each time the supplementary spare area is enlarged.

Moreover, even in optical recording mediums with assigned supplementary spare area as described above, defect sectors or blocks are registered in the PDL or SDL for defect area management. Accordingly, linear replacement and slipping replacement is utilized. However, for linear replacement, the optical pick-up must be transferred to and back from the spare area to the user area in order to record data for the defect blocks registered in the SDL within the assigned replacement blocks. Repetition of this may deteriorate the system performance. As a result, the optical medium is reformatted to move the defect sectors registered in the SDL to the PDL, thereby reducing the number of linear replacements and improving the system performance.

2.0

5

The reformatting method is classified into a full formatting through certification and a simple formatting by which the SDL is transferred to the G_2 -list of the PDL without certification process in order to reduce the formatting time. The P-list remains unchanged after the completion of the formatting but defective blocks of the SDL are stored as defective sectors in the G_2 -list. Thus, the G_2 -list may include defective sectors as well as normal sectors. Nevertheless, the normal sectors is considered as defect sectors.

The full formatting, shown in Fig. 5A, reads the old DMA information and certifies all data area other than the defect sectors registered in the P-list of the old PDL. Rather, the P-list of the old PDL is converted to the P-list of the new PDL without any change. Furthermore, a full formatting disposes of the G_1 -list and G_2 -list of the old PDL as well as the old SDL and then registers defect sectors found during the certification in the G_1 -list of the new PDL.

In contrast, the simple formatting, shown in Fig. 5B, converts the SDL to the G_2 -list without certification. Namely, the old DMA information is read and sectors in the P-list, G_1 -list and G_2 -list of the old PDL are converted to the P-list, G_1 -list and G_2 -list of a new PDL. Also, after converting the

old SDL entries to sixteen PDL entries, the converted SDL entries are disposed and the new PDL entries are registered in the G_2 -list of the new PDL.

Upon execution of a reformatting, the supplementary spare area is considered to be non-existent by the file system because the defect information of the SDL has been moved to the PDL. However, the location information of the supplementary spare area is maintained without change in the SDL block. Thus, an assignment of the supplementary spare area is still considered to be existent by the driver, namely the physical driver. Because the file system recognizes whether a formatting has been executed while the driver cannot, the file system and the driver have inconsistent information regarding the supplementary spare area. Accordingly, different judgements between the file system and driver regarding the supplementary spare area may cause problems in the system control.

Furthermore, a compatibility problem occurs when an optical recording medium as described above is transferred to other drivers. Specifically, when the optical recording medium is inserted into other driver, the driver first reads the DMA from the optical recording medium and informs the file system. Then, the file system constructs a new file system using the

information delivered from the driver. At this time, since the location information of the supplementary spare area is still recorded in the SDL block of the DMA, the location information is also sent to the file system together with the information from the driver. Accordingly, the file system regards that the supplementary spare area has been assigned. As a result, the area registered in the SDL block is considered to be actual supplementary spare area and is excluded when assigning the supplementary spare area or when executing linear replacement, thereby producing problems in compatibility.

SUMMARY OF THE INVENTION

Accordingly, an object of the present invention is to solve at least the problems and disadvantages of the related art.

An object of the present invention is to provide an optical recording medium in which the location information of a supplementary spare area registered in the DMA is reset after a formatting the optical recording medium.

Another object of the present invention is to provide a method of formatting an optical recording medium, which resets the location information of a supplementary spare area registered in the DMA when the optical recording medium is

5

formatted.

Additional advantages, objects, and features of the invention will be set forth in part in the description which follows and in part will become apparent to those having ordinary skill in the art upon examination of the following or may be learned from practice of the invention. The objects and advantages of the invention may be realized and attained as particularly pointed out in the appended claims.

To achieve the objects and in accordance with the purposes of the invention, as embodied and broadly described herein, a method of formatting an optical recording medium includes resetting the location information of the supplementary spare area and converting the assigned supplementary spare area to a writable area. In the present invention, the location information of the supplementary spare area is stored in a specific area of the optical recording medium. In the preferred embodiment, the location information of the supplementary spare area is stored in the SDL of the

BRIEF DESCRIPTION OF THE ATTACHED DRAWINGS

The invention will be described in detail with reference to the following drawings in which like reference numerals

refer to like elements wherein:

- Fig. 1 shows a structure of a general optical recording medium in the related art;
- Fig. 2A shows a slipping replacement algorithm in the
 for related art;
 - Fig. 2B shows a linear replacement algorithm in the related art;
 - Fig. 3 shows when a spare area is assigned at the top of the data area;
 - Figs. 4A and B show assigning and expanding supplementary spare area in a disc with a primary spare area as shown in Fig. 3;
 - Fig. 5A shows an example of a full formatting with certification:
 - Fig. 5B shows an example of a simple formatting without certification; and
 - Fig. 6 a flow diagram showing a method of formatting the optical recording medium according to the present invention.

DETAILED DESCRIPTION OF PREFERRED EMBODIMENT

Reference will now be made in detail to the preferred embodiments of the present invention, examples of which are illustrated in the accompanying drawings.

5

Generally, the present invention resets the location information of the supplementary spare area registered in the SDL block when an optical recording medium is formatted. Thus, the judgments of the file system and the driver would match with respect to the supplementary spare area. Fig. 6 is a flow diagram showing the operation of a driver when formatting the optical recording medium according to the present invention.

Referring to Fig. 6, upon receiving a formatting command (step 601), a judgement is made if a supplementary spare area has been assigned (step 602). If the supplementary spare area exists, the location information of the supplementary spare area recorded in the DMA is reset (step 603). To reset the location information of the supplementary spare area, any one of a variety of methods may be utilized. In one example, all the location information values of the supplementary spare area may be converted to the lowest value (for example, 00h) or the highest value (for example, FFh). In another example, the location information may be converted into a specific code value according to a predetermined agreement. That is, the location information value may converted to a value which would allow the file system to recognize that the location information of the supplementary spare area has been reset when the file system receives the DMA information from the

5

driver.

After resetting the location information of the supplementary spare area in step 603 or if a supplementary spare area has not been assigned as determined in step 602, a judgement is made whether the formatting is with certification (step 604). If the formatting is with certification, all sectors, including the sectors registered in the PDL and the SDL, is certified as shown in Fig. 5A (step 605). Thus, sectors judged to have defects are registered in the new PDL. On the other hand, if the formatting is judged to be without certification, all sectors registered in the SDL is registered in the new PDL without change as shown in Fig. 5B (step 606).

Upon completion of formatting as described above, the sectors of the supplementary spare area equivalent the defective sectors registered on the new PDL slips into and becomes a part of the user area to maintain the initial data recording capacity. At this time, recognizing that a formatting has been performed, the file system disposes the information of the supplementary spare area. Accordingly, the information of the supplementary spare area is disposed from both the driver and the file system after a formatting.

In the above embodiment, the location information of the supplementary spare area is reset prior to the formatting when

5

a formatting command is input. However, the location information of the supplementary spare area may be reset after the formatting. In such case, steps $604 \sim 606$ would proceed prior to steps $602 \sim 603$ when a formatting command is received in step 601.

Thus, according to the optical recording medium and method of formatting the optical recording medium in present invention, the location information of the supplementary spare area registered in the DMA is reset when the optical recording medium is formatted. This allows the judgements of the file system and the driver regarding the supplementary spare area to match, thereby leading to a consistent system control and maintenance of compatibility when the optical recording medium is transferred to different drivers.

The foregoing embodiments are merely exemplary and are not to be construed as limiting the present invention. The present teachings can be readily applied to other types of apparatuses. The description of the present invention is intended to be illustrative, and not to limit the scope of the claims. Many alternatives, modifications, and variations will be apparent to those skilled in the art.

5

What is claimed is:

- A method of formatting an optical recording medium comprising:
- (a) resetting a location information of a supplementary spare area; and
- (b) converting the supplementary spare area to a user area.
- 2. A method of claim 1, further comprises determining if a supplementary spare area has been assigned prior to (a) and (b), wherein resetting the location information of a supplementary spare area and converting the supplementary spare area to a user area, if a supplementary spare area has been assigned.
- 3. A method of claim 1, wherein (a) comprises converting the location information of the supplementary spare area to a predetermined value which indicates that the location information of the supplementary spare area has been reset.
 - 4. A method of claim 3, wherein the predetermined value

is a lowest value.

- A method of claim 3, wherein the predetermined value is a highest value.
- A method of claim 3, wherein the predetermined value is a specific code based upon a predetermined agreement.
 - 7. A method of claim 1, wherein in (b), registering sectors judged to have defects in a new PDL, if the formatting is with certification.
 - 8. A method of claim 1, wherein in (b), registering all sectors registered in an old SDL in a new PDL, if the formatting is without certification.
 - 9. A method of claim 1, wherein the location information of the supplementary spare area is stored in a SDL block of a DMA of the optical recording medium.

Abstract of Disclosure

An optical recording medium and method of formatting the optical recording medium is disclosed. In the present invention, the location information of the supplementary spare area, if assigned, is reset when the optical recording medium is formatted. The resetting of the location information results in consistency between a file system and a driver of the optical recording medium with respect to the supplementary spare area.

FIG.1 Related Art




FIG.2A Related Art




FIG.2B Related Art




FIG.3 Related Art



FIG.4 Related Art




FIG.5A Related Art




FIG.5B Related Art





FIG.6



BIRCH, STEWART, KOLASCH & BIRCH, LLP

COMBINED DECLARATION AND POWER OF ATTORNEY

PLEASE NOTE: YOU MUST COMPLETE THE FOLLOWING:

FOR PATENT AND DESIGN APPLICATIONS

ATTORNEY DOCKET NO. 465-656P

	ŧ

As a below named inventor, I hereby declare that: my residence, post office address and citizenship are as

Insert Title:	is named below) or an ori	ginal, first and joint invent	he original, first and sole invento: or (if plural inventors are named ght on the invention entitled:	r (if only one invento below) of the subjec				
	OPTICAL RECORDIN	G MEDTUM AND METHO	FOR FORMATTING					
Fill in Appropriate Information - For Use Without Specification Attached:	the specificat	is attached hereto. If not a ion was filed on pplication Number	ttached hereto,	as nd /or				
Attached:	the specificat	ion was filed on		as PCT				
	International A amended under	pplication Number PCT Article 19 on	; ; ; ; ; ; ; ; ; ; ; ; ; ; ; ; ; ; ;	ınd was licable)				
Insert Priority	I hereby state that I have reviewed and understand the contents of the above identified specification including the claims, as amended by any amendment referred to above. I acknowledge the duty to disclose information which is material to patentability as defined in Title 37 Code of Federal Regulations, §1.56. I do not know and do not believe the same was ever known or used in the United States of America befor my or our invention thereof, or patented or described in any printed publication in any country before my or our invention thereof or more than one year prior to this application, that the invention has not in public use on sale in the United States of America more than one year prior to this application, that the invention has no been patented or made the subject of an inventor's certificate issued before the date of this application in an country foreign to the United States of America on an application filed by me or my legal representatives or assigns more than twelve months (six months for designs) prior to this application, and that no application for patent or inventor's certificate base enflied in any country foreign to the United States of America on been filed in any country foreign to the United States of America prior to this application by me or my legal representatives or assigns, except as follows. I hereby claim foreign priority benefits under Title 55, United States Code, §119 (a)-(d) of any foreign application (s) for patent or inventor's certificate listed below and have also identified below any foreign application for patent or inventor's certificate having a filing date before that of the application on which							
Information: mi (if appropriate)	Prior Foreign Applicate 2127/1999	on(s) Korea	Tamus 22 1000	Priority Claimed				
	(Number)	(Country)	January 23, 1999 (Month/Day/Year Filed)	X D Yes No				
	(Number)	(Country)	(Month/Day/Year Filed)	Yes No				
	(Number)	(Country)	(Month/Day/Year Filed)	Yes No				
	(Number)	(Country)	(Month/Day/Year Filed)	Yes No				
nsert Provisional	(Number) I hereby claim the ber application(s) listed below	(Country) nefit under Title 35, United	(Month/Day/Year Filed) States Code, §119(e) of any Uni	Yes No				
Application(s):	(Application Number)		(Filing Date)					
	(Application Number)		(Filing Date)					
nsert Requested nformation:	All Foreign Applications, Months for Designs) Prio	r To The Filing Date of T		Than 12 Months (6				
usert Prior U.S.	prior United States applica §112, I acknowledge the du Code of Federal Regulation	the subject matter of each tion in the manner provide ity to disclose information v	States Code, §120 of any United of the claims of this application id by the first paragraph of Title 35 which is material to patentability iniable between the filing date of is application:	s not disclosed in the , United States Code as defined in Title 37				
application(s):	(Application Number)	(Filing Date)	(Status - patented, p	nding, abandoned)				

(Filing Date)

(Status - patented, pending, abandoned)

(Application Number)

I hereby appoint the following attorneys to prosecute this application and/or an international application based on this application and to transact all business in the Patent and Trademark Office connected therewith and in connection with the resulting patent based on instructions received from the entity who first sent the application papers to the attorneys identified below, unless the inventor(s) or assignee provides said attorneys with a written notice to the contrary.

Terrell C. Birch	(Reg. No. 19,382)	Raymond C. Stewart	(Reg. No. 21,066)
Joseph A. Kolasch	(Reg. No. 22,463)	James M. Slattery	(Reg. No. 28,380)
Bernard L. Sweeney	(Reg. No. 24,448)		(Reg. No. 29,680)
Charles Gorenstein	(Reg. No. 29,271)		
Leonard R. Svensson	(Reg. No. 30,330)	Terry L. Clark	(Reg. No. 32,644)
Andrew D. Meikle	(Reg. No. 32,868)	Marc S. Weiner	(Reg. No. 32,181)
Joe McKinney Muncy	(Reg. No. 32,334)	Andrew F. Reish	(Reg. No. 33,443)
C. Joseph Faraci	(Reg. No. 32,350)	Donald J. Daley	(Reg. No. 34,313)

Send Correspondence to:

PLEASE NOTE:

FOLLOWING:

YOU MUST COMPLETE THE

100

BIRCH, STEWART, KOLASCH & BIRCH, LLP

P.O. Box 747 • Falls Church, Virginia 22040-0747 Telephone: (703) 205-8000 • Facsimile: (703) 205-8050

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 100 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

	Full Name of First or Sole Inventor:	GIVEN NAME	FAMILY NAME	INVENTOR'S SIGNATURE		DATE*
ű	Insert Name of Inventor Insert Date 1 his	Yong Cheol	DZDK	Park You che	0	
Ĵ	Document is Signed	Residence (City, State		Jank long che	CITIZENSHIP	Nov. 22, 1999
4	Insert Residence Insert Citizenship	Kyonggi-do,	Korea		Republic	- 6 -
1		POST OFFICE ADDRE	SS (Complete Street Address	s including City, State & Country)	Republic	or Korea
4	Insert Post Office Address	Jugong APT.	. 215-204, Wonmun	-dong, Kwachon-shi,	Kyonggi-do,	Korea
ent ent	Full Name of Second Inventor, if any:	GIVEN NAME	FAMILY NAME	INVENTOR'S SIGNATURE		DATÊ
1	see above	Residence (City State	& Country)		CITIZENSHIP	
10			SS (Complete Street Address	s including City, State & Country)	L	
	Full Name of Third Inventor, if any	GIVEN NAME	FAMILY NAME	INVENTOR'S SIGNATURE		DATE*
	sec above	Residence (City, State	& Country)	1	CITIZENSHIP	
		POST OFFICE ADDRE	SS (Complete Street Address	s including City, State & Country)	1	
	Full Name of Fourth Inventor, if any	GIVEN NAME	FAMILY NAME	INVENTOR'S SIGNATURE		DATE*
	see above	Residence (City, State	& Country)	1	CITIZENSHIP	
		POST OFFICE ADDRE	SS (Complete Street Address	s including City, State & Country)	<u> </u>	
	Full Name of Fifth Inventor, if any see above	GIVEN NAME	FAMILY NAME	INVENTOR'S SIGNATURE		DATE*
	300 40010	Residence (City, State	& Country)		CITIZENSHIP	
		POST OFFICE ADDRE	SS (Complete Street Address	s including City, State & Country)	1	
	Page 2 of 2 (USPTO Approved 3-90) (Revised 8-97)	* DATE OF SIGNATURE				-